1393

April 2025

Time - Three hours (Maximum Marks: 100)

- [N.B. 1. Answer all questions under Part-A. Each question carries 3 marks.
 - Answer all the questions either (a) or (b) in Part-B. Each question carries 14 marks.]

PART - A

- List out the types of approximate estimate.
- Compute the material requirements for Cement Concrete 1:2:4 -1m³ (using 20mm aggregates) using thumb rule.
- Write short notes on Lump sum provision.
- Write about wall plastering.
- Prepare detailed quantity for 150 mm thick RCC roof slab of room size 5m×4m.
- Write short notes on contingencies.
- Write any three abbreviations in group system.
- Write about the columns in dimension paper.
- 9. What is sinking fund?
- Define standard rent.

PART - B

11. (a) The actual expenditure incurred in the construction of a single storey residential building of plinth area 98m² is found to be Rs. 28,55,000 in which 55% towards the cost of materials and remaining is towards the cost of labour. It is now proposed to construct a similar building of same height and specification with the plinth area of 74m² at the place where the cost of materials are 13% more and cost of labour is 19% less. Estimate approximately the cost of proposed building.

(Or)

(b) Explain the steps involved in writing standard specification.

[Turn over.....

12. (a) Prepare the data for RCC beam of size 300 x 450mm with CC 1:2:4 mix using 20mm hard broken stone with reinforcement at 150 kg of steet/m³ including centering, shuttering etc. complete - 1 m³.

RCC beam of size 300 x 450mm with CC 1:2:4 mlx using 20mm hard broken stone with reinforcement at 150kg of steel/m³ including centering, shuttering etc. complete - 1 m³.

Cement concrete 1:2:4 - 1 m³
Steel - 150kg

Binding wire - 1% of reinforcement

Bar bending/cutting bending - 150 kg

and tying grills

Centering or shuttering 8.89 m²

Materials and labour required:

CC 1:2:4 using 20mm hard broken stone - 10m³

Broken stone 20mm size - 9.00 m³
Sand - 4.5 m³
Cement - 3240 kg
Mason I class - 3.5 Nos.
Mazdoor category I - 21.2 Nos.
Mazdoor category II - 35.3 Nos.

Cost of materials and labours at site (in Rupees)

Cement - 6500.00/tonne Steel - 60000.00/ tonne

Binding wire - 62.00/kg Broken stone 20mm size - 960/m³

Sand - 1000.00/m³

Mason I class - 850.00 each/day
Mazdoor category I - 650.00 each/day
Mazdoor category II - 600.00 each/day

Cutting, bending and tying - 3000/100 kg

grills

Centering or shuttering - 150.00/m²

charges

Mortar mixing charges - 100.00/m³

(Or)

(b) Prepare the data for Pointing with C.M 1:3 for R.R masonry = 10 m^2 Pointing with C.M 1:3 for R.R masonry = 10 m^2

 Cement
 = 34 kg

 Sand
 = 0.09 m³

 Mason II class
 = 1.60 Nos.

 Mazdoor I class
 = 0.50 Nos.

 Mazdoor II class
 = 1.10 Nos.

 Mixing charge
 = 10m³

Cost of materials and labour

Cement = Rs. 5200/tonne Sand - Rs. 520/ m³

Mason II class - Rs. 480 each per day
Mazdoor I class - Rs. 400 each per day
Mazdoor II class - Rs. 380 each per day

Mixing charges - $Rs.300/ m^3$

13. (a) Take out the quantities for the RCC works with CC 1:2:4 mix using 20mm HBS for "Community hall with RCC columns & T-beams" from Sketch-1 by Trade system. Assume any other data if necessary.

(Or)

- (b) Take out the quantities for the Brickwork with CM 1:5 in super structure for "Community hall with RCC columns & T-beams" from Sketch-1 by Trade system. Assume any other data if necessary.
- 14. (a) Prepare the detailed estimate of quantities for ceiling plastering with C.M 1:3 for "A small residential building with three rooms with R.C.C roof" given in Sketch -2 by Group system.


(Or)

- (b) Prepare the detailed estimate of quantities for wall plastering with C.M 1:5 for "A small residential building with three rooms with R.C.C roof" given in Sketch -2 by Group system.
- 15. (a) Write a typical report to accompany the estimate for the construction of Foot over bridge.

(Or)

(b) A newly constructed building stands on a plot costing Rs.20 lakhs. The construction cost of the building is Rs.30 lakhs and the estimated life of the building is 65 years. The investor desires to have 10 % return on the construction cost and 6 % return on the land cost. Assuming annual repairs to be at 0.3 % of the construction cost and other outgoings at 25% of the gross rent. Calculate the monthly rent that will have to be charged for the building. Interest on sinking fund is 2 %.

SKETCH-1



SKETCH - 2

